



- NOTES:
1. MATERIAL: NYLON 6/6 UL 94 V-0 (RMS-019)
  2. COLOR: BLACK.
  3. TO FIT IN A  $\varnothing 7.9 \pm .002$  [ $\varnothing 0.313 \pm 0.05$ ] THREADED HOLE.  
 MINIMUM RECOMMENDED PANEL THICKNESS: 6 mm [.236]  
 PART CAN ALSO FIT NON THREADED HOLE DIA. 7 mm [.276]
  4. PART DESIGNED IN mm, ALTERNATE UNITS FOR REFERENCE ONLY.
  5. TOOL REQUIRED FOR INSTALLATION, AND PHILIPS SCREWDRIVER FOR REMOVAL.

A			RELEASED FOR PRODUCTION			SK 12/19/08		TITLE: <b>BARBED PUSH FASTENER, REMOVABLE</b>				DWG IN mm [IN]					
REV.			DESCRIPTION			ENGR. DATE		<small>CREATED USING SOLIDWORKS</small> <small>GENERAL TOLERANCE UNLESS OTHERWISE NOTED</small> <small>±0.25</small> <small>ANG. ±1°</small>		FILE #: BPFR-1 SHEET: 1 OF 1 SHEET SIZE: A RE: RICHCO, INC., --		DWN: SK DT: 07/01/08 APP: S.K. CHKD: D.Z.		FINAL PART #		PRINT TYPE <b>CA</b>	
								RICHCO, INC. ENG@RICHCO-INC.COM (773) 539-4060		BPFR-1							