



| PART NO. | MAXIMUM PANEL THICKNESS | HOLE DIAMETER | "A"±.020 | "B" REF |
|----------|-------------------------|-------------------------|--------------|-------------|
| PGM-1 | .062 [1.57] | .250±.003 [6.35±0.08] | .312 [7.9] | .312 [7.9] |
| PGM-2 | | .312±.003 [7.9±0.08] | .375 [9.5] | |
| PGM-3 | | .468±.002 [11.9±0.05] | .531 [13.5] | |
| PGM-4 | .067 [1.7] | .189±.004 [4.8±0.1] | .236 [6] | .205 [5.2] |
| PGM-5 | .062 [1.57] | .500±.002 [12.7±0.05] | .562 [14.3] | .250 [6.35] |
| PGM-6 | .067 [1.7] | .252 [6.4±0.1] | .299 [7.6] | .221 [5.6] |
| PGM-7 | .063 [1.6] | .278±.002 [7.05±0.05] | .433 [11] | .276 [7] |
| PGM-8 | | .307±.008 [7.8±0.2] | .375 [9.5] | .236 [6] |
| PGM-9 | | .376±.002 [9.55±0.05] | .511 [13] | .256 [6.5] |
| PGM-10 | .386±.008 [9.8±0.2] | .236 [6] | | |
| PGM-11 | .062 [1.57] | .531±.002 [13.48±0.05] | .593 [15.1] | .250 [6.35] |
| PGM-12 | | .625±.002 [15.9±0.05] | .718 [18.2] | |
| PGM-13 | | .506±.006 [12.85±0.15] | .669 [17] | |
| PGM-14 | .062 [1.57] | .750±.002 [19.05±0.05] | .843 [21.4] | .250 [6.35] |
| PGM-15 | .781±.002 [19.84±0.05] | .890 [22.6] | | |
| PGM-16 | .079 [2] | .628±.002 [15.95±0.05] | .787 [20] | |
| PGM-17 | .062 [1.57] | .875±.002 [22.22±0.05] | .968 [24.6] | .250 [6.35] |
| PGM-18 | .125 [3.2] | 1.250±.002 [31.75±0.05] | 1.375 [34.9] | .465 [11.8] |
| PGM-19 | | .746±.002 [18.95±0.05] | .925 [23.5] | .413 [10.5] |
| PGM-20 | | 1.375±.002 [34.93±0.05] | 1.500 [38.1] | .465 [11.8] |
| PGM-21 | | 1.750±.002 [44.45±0.05] | 1.906 [48.4] | |
| PGM-22 | .118 [3] | .864±.002 [21.95±0.05] | 1.024 [26] | .378 [9.6] |
| PGM-23 | .125 [3.2] | 2.000±.002 [50.8±0.05] | 2.170 [55.1] | .470 [11.9] |
| PGM-24 | | .500±.002 [12.7±0.05] | .578 [14.7] | .406 [10.3] |
| PGM-25 | | 1.004±.004 [25.5±0.1] | 1.102 [28] | .500 [12.7] |
| PGM-26 | | .562±.002 [14.27±0.05] | .656 [16.7] | .406 [10.3] |
| PGM-27 | | .625±.002 [15.88±0.05] | .718 [18.2] | |
| PGM-28 | | .687±.002 [17.45±0.05] | .781 [19.8] | |
| PGM-29 | | .875±.002 [22.22±0.05] | 1.125 [28.6] | .453 [11.5] |
| PGM-30 | | 1.203±.002 [30.55±0.05] | 1.339 [34] | .512 [13] |
| PGM-31 | | 1.500±.002 [38.1±0.05] | 1.671 [42.4] | .465 [11.8] |
| PGM-32 | | 1.097±.004 [27.86±0.1] | 1.218 [30.9] | |
| PGM-33 | .375±.002 [9.5±0.05] | .468 [11.9] | .406 [10.3] | |
| PGM-34 | .437±.002 [11.1±0.05] | .531 [13.5] | | |

NOTES:

- MATERIAL: NYLON 6/6 UL 94 V-2 (RMS-01).
-NYLON 6/6 UL 94 V-0 (RMS-19),
AVAILABLE BY SPECIAL ORDER ONLY. TO ORDER, ADD SUFFIX "-V0"
- COLOR: BLACK.
COLOR WHITE AVAILABLE BY SPECIAL ORDER ONLY.

| | | | | | | |
|---|---|---|---|---------------|----------------------------|----------------------------|
| TITLE: PUSH GROMMET HOLE PLUG [M SERIES] | | | | | DWG IN IN [MM] | |
| CREATED USING SOLIDWORKS | | | FILE #: PGM | DWN: SK | APP: SK | FINAL |
| TOLERANCES UNLESS NOTED XX=±.010 .XXX=±.005 FRAC.=±1/64 ANG.=±1° | | | SHEET: 1 OF 1 | SHEET SIZE: A | DT: 02/14/08 | CHKD: D.Z |
| RE: RICHCO, INC. | | | RICHCO, INC. ENG@RICHCO-INC.COM (773) 539-4060 | | PART # SEE TABLE | PRINT TYPE CA |
| G SEE CO 200442 FOR CHANGES SK 09/21/09 | F SEE CO 200321 FOR CHANGES SK 02/09/09 | - SEE ENGINEERING FOR REV A-E - ENGR. DATE | | | | |